



Matriale:

MESSING IHT. EN12164

Produksjonsmetode:

Formstøpt

Tekniske begrensninger:

Arbeidsmiljøtemperatur:

Område: -20~+150°C


Maks trykk: PN25

Funksjoner:

Gjenger i ISO 228-1 standard. (BSP)

Brukes til varmt og kaldt vann, olje, luft, damp, etc.

**f BRØDR.
FREBERG AS**



DT			A	B	C	SW	GRS
1/2" x 3/8"	500	10	21,5	3/8"	1/2"	21	30
3/8" x 1/2"	450	10	21,5	1/2"	3/8"	25	31
3/4" x 1/2"	280	10	24	1/2"	3/4"	26,5	45
1/2" x 3/4"	280	10	25	3/4"	1/2"	30	52
1/2" x 1"	200	10	28	1"	1/2"	37	82
1" x 3/4"	150	5	27	3/4"	1"	33,5	81
3/4" x 1"	160	10	29,5	1"	3/4"	37	79
1" x 1 1/4"	105	5	32	1 1/4"	1"	47	107
1" x 1 1/2"	75	5	34	1 1/2"	1"	52	151,5
1 1/4" x 1 1/2"	70	5	36	1 1/2"	1 1/4"	52	156
1" x 2"	115	5	38	2"	1"	64	268
1 1/4" x 2"	110	5	40	2"	1 1/4"	64	270
1 1/2" x 2"	110	5	40,5	2"	1 1/2"	64	245